



INTERACTIVE | CENTRAL VACS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DST. AUDIO | STRUCT. WIRE | TOOLS | INFO

A/V AND COMMUNICATIONS DISTRIBUTED AUDIO



ATL AA120



ATL AM1200



BOG C35



CSI PVL30A



BOG SM4T



CSI MGS1



CSI TS8

Paging Amps



ATL AA120 6CH 120W Mixer Amplifier
ATL AA60 3CH 60W Mixer Amplifier

SOUND MASKING DEVICES

ATL AM1200
 Self-Contained Sound Mask System



CLASSIC SERIES PA AMPLIFIERS

Provide mixing of microphones, telephone and auxiliary sources - Output jacks allow addition of tape recorder or an additional booster.

- BOG C10** 10-watt, 3 input
- BOG C20** 20-watt, 3 input
- BOG C35** 35-watt, 4 input
- BOG C60** 60-watt, 4 input

GOLD SERIES AMPLIFIERS

BOG GS60
 60 watts, 7 input - 4 ohm, 8ohm, 25VCT, 25V and 70V output - Dual function 10-band graphic eq. - Variable loudness contour control - Phantom power - Resettable circuit breaker - Rack mount w/ GSRPK.

BOG GS150D
 150 Watt Dual Equalizer Paging Amp, Class D

- 4 dedicated MIC inputs
- 1 selectable MIC/TEL input
- 1 selectable MIC/AUX input
- 1 dedicated AUX input
- 4-ohm, 8-ohm, 25V, 25VCT, and 70V transformer-coupled outputs
- Rack mountable - 2RU package
- Dual-function, 10-band graphic equalizer (Acoustic EQ or Feedback Control modes)
- True loudness contour function
- Audio Enhancement circuit for improved intelligibility
- Switchable phantom power supply (13VDC)
- Variable AUX input muting
- Remote master volume control capability
- Automatic level control



PVL Series

PVL series amplifiers offers features such as priority paging and multiple, easily accessible source inputs, at a budget-minded price. These amplifiers are perfect for small installations such as classrooms, retail shops, convenience stores, or for use with the Digital Deterrent™ feature incorporated into most of Speco Technologies' DVRs. These amplifiers have commercial and residential outputs and are extremely versatile. 5 year warranty.

CSI PVL15A

15W P.A. Amplifier

- Frequency Response: 30Hz - 20kHz
- RMS Power: 15W
- Max. Power: 30W
- Outputs: 4 and 8 Ohms, 70/25V
- AC Voltage: 120 VAC 50/60Hz
- Microphone Inputs: 2 (One 1/4" and one 1/4" or XLR)
- Auxiliary Inputs: 1 (One 1/4")

CSI PVL30A

30W P.A. Amplifier

- Frequency Response: 30Hz - 20kHz (±3dB)
- RMS Power: 30W
- Max. Power: 60W
- Outputs: 4 and 8 Ohms, 70/25V
- AC Voltage: 120 VAC 50/60Hz
- Microphone Inputs: 2 (One 1/4" and one 1/4" or XLR)
- Auxiliary Inputs: 1 (One 1/4" or RCA stereo)

CSI P30FA

30W PA Amplifier with AM/FM Tuner

- 30 Digital station preset FM/AM tuner
- Built-in telephone paging
- Voice activated priority paging, and music on hold circuits
- Input connections include two locking Cannon type XLR connectors, one 1/4" microphone connector, one RCA aux input
- Outputs include 4 ohm, 8 ohm, and 25/70 volt
- 30 Watt RMS at less than 1.0% distortion
- Dual voltage 117/220V AC for 50/60 Hz
- A rack mounting kit is included

CSI P60FACD

60W PA Amplifier with AM/FM Tuner and CD player

- UL LISTED
- FM/Am Tuner with 8 Function CD player
- 60 Watt RMS/ 90 Watt Max
- AC 115V/230V 50/60Hz
- Frequency Response: 60-15kHz
- 4 MIC inputs (1mV; 250 ohm)
- 1 AUX Input (200mV 47K)
- 1 Telephone (.1-1V 600 ohm)
- 4/8/16 ohms & 25/75 V line Outputs
- Music on Hold Feature
- Separate Bass and Treble controls

CSI PBM30

30W Contractor Series PA Amplifier

- Auto mute function
- Music on hold output with separate level control (600 ohm line and one watt 8 ohm)
- 600 ohm telephone line input with level control
- Accepts inputs from two microphones
- A source can also be connected via an auto summing stereo auxiliary RCA input
- Outputs include a choice of 4, 8, and 16 ohm as well as 70 and 25 volt line outputs
- UL listed

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

CSI PL200M

160W Matrix Amplifier with 5 Source and 4 Zones

- Simultaneous playback of up to 5 sources into 4 zones
- 40W RMS per zone for 160W total RMS power
- Telephone paging function and monitor output for music-on-hold feature
- Microphone 1 priority with VOX mute function
- Intelligent cooling fan
- RoHS compliant
- Separate controls (gain, bass, treble, volume) and LED indicator for each zone
- 19" Rack mount design with built-in handles (3U)

CSI PL260A

260W PA Amplifier

- 260 Watts RMS Power
- Seven 70 or 25 Volt zone outputs with 70/25 switch selector
- 24 Volt input for emergency Back Up power
- 5 XLR MIC connector inputs w/individual Phantom Power switches
- 3 Auxiliary inputs
- Pre-amp input/booster output
- Additional auxiliary output
- 4/8/16 Ohm output zone
- Music on hold feature
- 1 Telephone paging input (0.1-1V 600 ohm)
- AC 117V 60Hz
- Seven zone on/off selectors on face plate
- Separate bass and treble controls
- CSA & UL approved

CSI PMM120A

120W PA Amplifier with 6 Inputs

- UL LISTED
- 120 Watt RMS
- AC 120V, 50/60Hz
- Frequency Response: 50-15kHz
- 6 MIC Inputs, 4 XLR Connectors (1.0mv/250 Ohms)
- 1 Aux Input (200mV 47K)
- 1 Telephone (0.1-1V 600 ohm)
- 4/8/16 ohms & 75/25 V Line Inputs
- Music on Hold Feature
- Separate Bass and Treble Controls.

CSI PMM60A

60W PA Amplifier with 6 Inputs

- UL LISTED, 60 Watt RMS
- AC 120V, 50/60Hz
- Frequency Response: 50-15kHz
- 6 MIC Inputs, 4 XLR Connectors (1.0mv/250 Ohms)
- 1 Aux Input (200mV 47K)
- 1 Telephone (0.1-1V 600 ohm)
- 4/8/16 ohms & 75/25 V Line Inputs
- Music on Hold Feature
- Separate Bass and Treble Controls

Speakers & Accessories:



PAGING SPEAKERS

ATL APX40TN

40 Watt Horn Speaker w/Integrated 25V/70V/100V Transformer

ATL FAP40T

Strategy2- 4" Ceiling Speaker Sys, Each

ATL FAP62T

Strategy2 - 6" 2-Way Ceiling Speaker Sys, Each

ATL GD87W

8"Coax Ceiling Speaker w/Grill

ATL SD72WV

8" Dual Cone Ceiling Speaker w/Grill and Volume Control

ATL SM42TB

Outdoor 70V/8 OHM, 4" 2-Way Speaker, Black - Each

ATL SM42TWH

Outdoor 70V/8 OHM, 2way Speaker, White - Each

SPEAKER ACCESSORIES

ATL AT35

35W Attenuator Single Gang

ATL AT35D

35W Decora Attenuator with Ivory/White Trim and Knobs



PAGING SPEAKERS

BOG SM4T

Surface Mount Easy Install™ Speaker 4 watt multitap - Mounting studs are also speaker wiring connectors -- No need to cut ceiling tile holes.

BOG S86T725PG8W

8" Flush Ceiling Mount speakers with 6 power taps, integral transformer, and white steel grill

BOG S86T725PG8WVK

Same as above with integral volume control knob

BOG SPT15A

15 Watt paging horn speaker with integral transformer, weatherproof, and multi-tap

BOG WBS8T725V

8" Wall Baffle Speaker Volume control

BOGEN ACCESSORIES

BOG MGN19

Industrial Gooseneck Omni-directional Microphone

BOG AT10A

10 watt attenuator on a single gang aluminum plate

BOG AT35A

35 watt attenuator on a double gang aluminum plate

BOG RE84

In-Ceiling 8" Speaker back can

BOG TB8

Tile Bridge for 8" In-Ceiling speakers



CSI G86TG

8" Flush mount ceiling speaker with grill

CSI G86TCG

8" Flush mount ceiling speaker with integral volume control and grill

CSI SPC15T

15 Watt paging horn speaker with integral transformer

CSI SP5MAT

Multi-Application Ceiling Speakers - Preassembled with back can and mount transformer - 5.25" woofer with 1" tweeter - 30 watt - 8 wattage taps

CSI SP6MAT

Same as SP5MAT with 6.5" woofer, 40 watts, and 9 wattage taps

CSI SPG86T

8" 70V Ceiling speakers with built-in transformer, grill, and mounting brackets- no T-bar brackets or top hat back boxes necessary

SPEAKER ACCESSORIES

CSI MGS1

Industrial Gooseneck Omni-directional Microphone

CSI WAT10

10 watt attenuator on a single gang aluminum plate

CSI TS8

Tile bar for 8" in-ceiling speakers