

# DS778 Long Range PIR Detector

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Motion Analyzer II processing
- ▶ Pointable mirrored optics
- ▶ Q-map signal processing
- ▶ Long range coverage
- ▶ Four mounting options

The wall mount, long range DS778 PIR Detector uses Motion Analyzer II signal processing to reduce false alarms. To aid in walk testing, the DS778 features a high efficiency alarm LED that is visible throughout the coverage pattern. This allows one installer to install and test the detector. The detector's internally pointable optics and mounting options provide installation flexibility.

## Functions

### Signal Processing

Motion Analyzer II uses multiple thresholds and timing windows to analyze timing, amplitude, duration, and polarity of signals to make an alarm decision. Will not alarm on extreme levels of thermal and illumination disturbances caused by heaters and air conditioners, hot and cold drafts, sunlight, lightning, and moving headlights. Two sensitivity settings are provided.

### Test Features

The high efficiency alarm LED can be seen throughout the walk test area. Internal noise voltage test pins provide precise pattern location and background disturbance evaluation using a standard analog meter.

## Insect and Draft Immunity


The sealed optical chamber provides immunity to drafts and insects.

## Certifications and approvals

Europe Complies with EN50131-1, Grade 2

Region	Certification	
Europe	CE	DS778
USA	UL	ANSR: Intrusion Detection Units (UL639) DS778

## Installation/configuration notes



### Top View

Long Range Coverage 60 m x 4.5 m (200 ft x 15 ft)



### Side View

**Long Range Coverage 60 m x 4.5 m (200 ft x 15 ft)****Technical specifications****Enclosure Design**

Dimensions:	14.6 cm x 9.5 cm x 6.35 cm (5.75 in. x 3.75 in. x 2.5 in.)
Material:	High impact ABS plastic enclosure

**Environmental Considerations**

Operating Temperature:	-40°C to +49°C (-40°F to +120°F) <i>For UL Listed Applications, 0°C to +49°C (+32°F to +120°F)</i>
Radio Frequency Interference (RFI) Immunity:	No alarm or setup on critical frequencies in the range from 26 MHz to 950 MHz at 50 V/m.

Complies with Environmental Class II (EN50130-5)

**Mounting**

Height Range:	Recommended 2 m to 2.6 m (6.5 ft to 8.5 ft)
Internal Pointability:	Coverage is adjustable $\pm 10^\circ$ horizontally, $+2^\circ$ to $-18^\circ$ vertically.

**Outputs**

Alarm:	Form C contacts rated at 3.0 W, 125 mA at 28 VDC for resistive loads.
Tamper:	Normally-closed. Contacts rated at 28 VDC, 125 mA maximum.

**Power Requirements**

Current Draw:	18 mA at 12 VDC
Voltage:	6 VDC to 15 VDC

**Ordering information****DS778 Long Range PIR Detector**

Provides PIR 60 m x 4.5 m (200 ft x 15 ft) coverage.  
Order number **DS778**

**Accessories****B328 Gimbal-mount Bracket**

Mounts on a single-gang box and allows rotation of a detector. Wires are hidden inside.  
Order number **B328**

**B335-3 Swiveling low-profile mount**

Swiveling, low-profile, universal bracket for wall mounting. The vertical swivel range is  $+10^\circ$  to  $-20^\circ$ , while the horizontal swivel range is  $\pm 25^\circ$ .  
Order number **B335-3**

**B338 Universal Ceiling-mount Bracket**

Swiveling universal bracket for ceiling mounting. The vertical swivel range is  $+7^\circ$  to  $-16^\circ$ , while the horizontal swivel range is  $\pm 45^\circ$ .

Order number **B338**

**TC6000 Test Cord**

Test cord for connecting a compatible detector's test pins to a voltmeter. It is 4.6 m (15 ft) long.

Order number **TC6000**

**Represented by:**

**North America:**

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security  
Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**

Bosch (Shanghai) Security Systems Ltd.  
203 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**Latin America and Caribbean:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com