Dual Voltage Box/Bracket*



- Dual Voltage Capability
- Accepts a two-gang face plate.
- 3/4" Resi-Rings
- Backless Design accommodates large/deep low voltage devices.
- Eliminates cutting the backs off Electrical Boxes.
- Accommodates bend radius requirements for low voltage cabling.
- Provides ample space for installation.

Part No.	Cover	Volume	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SC200DV	1-Gang	20.5 cu. in	16	6.4




Low Voltage Add-On Bracket*



- Dual Voltage Capability accommodates high and low voltage devices in the same box.
- Attaches to virtually any nonmetallic electrical box as long as there's a side for the tape to stick to.

Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SC100SC	1-Gang	24	2.3



- Accepts a two-gang face plate.
- 3/4" Resi-Rings
- Allows for the installation of most decora style yoke plates



Low Voltage Adjustable Brackets*



- Accommodates varying finished wall thicknesses ideal for wood paneling, tile or stucco walls.
- With the turn of a screw, adjust to any wall thickness.
- Steel Mounting Bracket provides a secure mount.
- Backless Design accommodates large/deep low voltage devices.

Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SC100ADJC	1-Gang	24	7.5
SC200ADJC	2-Gang	20	6.9



- Eliminates cutting the backs off Electrical Boxes.
- Accommodates bend radius requirements for low voltage cabling.
- Provides ample space for installation.
- Removable Bracket and Interchangeable Mounting Bracket – upgrade from a one-gang to a two-gang anytime.

*U.S. Patent 5,289,934

Low Voltage Divider Plate **71**°



Part No.	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SCDIV	50	2.2

For use with Carlon® SuperBlue™ boxes only (Refer to page 117)

Mud Ring (4" sq. 1/2" Raised Cover)



Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SCA410	1-Gang	20	1.54

NOTE: Classified for two hour fire resistive wall assemblies when used with Two-Gang Quick Connect Outlet and Switch Boxes

^{*}U.S. Patent D463,376