

## Resi-Gard™ Flexible Raceway

Ideal for providing a main chase from the main distribution panel to a secondary hub in the attic or basement. Resi-Gard™ non-metallic flexible raceway is available in 3/4" to 2" diameter sizes with factory installed pull tape in sizes 1" to 2". The raceway is hand bendable, lightweight and easily cut to length to reduce scrap. Bright orange color clearly signifies a low voltage installation.



**UL**  
LISTED  
E151168  
FT-1

### Standard Length Coils

Catalogue No.	Size (in.)	Pull Tape	Coil Length	Prod. Wt. (lb.) Coil
SCE4X1-100	3/4	Empty	100	11.5
SCF4X1C-100	1	900 lb.	100	17.9
SCG4X1C-100	1-1/4	900 lb.	100	21.5
SCH4X1C-50	1-1/2	900 lb.	50	11.2
SCJ4X1C-50	2	900 lb.	50	13.4

### Standard Length Reels

Catalogue No.	Size (in.)	Pull Tape	Reel Length	Prod. Wt. (lb.) Coil
SCE4X1-1000	3/4	Empty	1000	115.0
SCF4X1C-1500	1	900 lb.	1500	268.5
SCJ4X1C-500	2	900 lb.	500	133.5

## Resi-Gard™ Fittings

A complete line of Carlton® one-piece quick connect couplings, threaded adapters and snap-in terminator adapters are available for quick, easy professional installation of Resi-Gard™ flexible raceway.

### Quick Connect Couplings



Cat. No.	Size (in.)	Std. Ctn. Qty	Std. Ctn. Wt. (lb.)
SCA240E	3/4	25	0.783
SCA240F	1	20	0.972

### Quick Connect Threaded Adapters



Cat. No.	Size (in.)	Std. Ctn. Qty	Std. Ctn. Wt. (lb.)
SCA243E	3/4	25	0.633
SCA243F	1	20	0.778

### Quick Connect Snap-In Adapters



Cat. No.	Size (in.)	Std. Ctn. Qty	Std. Ctn. Wt. (lb.)
SCA253E	3/4	25	0.783
SCA253F	1	20	0.918

### Male Terminal Adapters\*



Cat. No.	Size (in.)	Std. Ctn. Qty	Std. Ctn. Wt. (lb.)
SCE943G	1-1/4	50	3.0
SCE943H	1-1/2	25	2.5
SCE943J	2	50	6.8

### Standard Couplings\*



Cat. No.	Size (in.)	Std. Ctn. Qty	Std. Ctn. Wt. (lb.)
SCE940G	1-1/4	30	3.5
SCE940H	1-1/2	25	3.9
SCE940J	2	30	5.2

\* Must be cemented to Resi-Gard™ Flexible Raceway using ONLY Resi-Gard™ Solvent Cement.