

DTK-CAT6A Series

10 Gigabit Ethernet Surge Protection



Product Features

- Primary protector for communications circuits
- Available with 110-Shielded RJ connections
- Compatible with CAT5E, CAT6 and CAT6A circuits
- Protects all four pairs
- Multi-stage SAD technology with hybrid design provides the best possible protection
- Automatically resets to protect against multiple surges

Applications

- Data Networks
- IP Video Cameras
- Point of Sale Terminals
- Wireless Access Points

Accessories

- DIN Rail Mounting Kit – Part Number DTK-DRK

DITEK's CAT6A Surge Protective Devices (SPD's) are specifically designed for the demanding requirements of today's network infrastructure. Available with 110-to-110 and 110-to-RJ connections; they provide maximum protection for IP and PoE circuits transmitting video and/or data over CAT5e, CAT6 or CAT6A cable. DITEK's CAT6A products are suitable for use on all network connected equipment.

Technical Specifications

Part Numbers:	DTK-110C6A	DTK-110C6APOE
	DTK-110RJ6A	DTK-110RJ6APOE
Service Voltage:	0-12V	48V
MCOV:	18V	64V
Clamping Voltage:	21.6V	72V
Protection Modes:	Line-Ground (All)	
Surge Current Rating:	100A /pair (10/1000 μ s)	30A /pair (10/1000 μ s)
Max Continuous Current:	1.6A/port	
Power Handling:	19.2 Watts/port	76.8 Watts/port
Data Rate:	10 Gbps	

Mechanical Characteristics

Connection Method:	110C6A/110C6APOE: 110-to-110 110RJ6A/110RJ6APOE: 110-to-RJ
Housing:	ABS
Operating Temperature:	-40°F - 158°F (-40°C - 70°C)
Maximum Humidity:	95% non-condensing
Dimensions:	5.4"L x 3.3"W x 1.3"H (137mm x 84mm x 33mm)
Weight:	7.2 oz. (202 g)

Quality, Standards & Approval

Agency Approvals:	UL497, UL497B
Standards Compliance:	CAT6A, TIA-568-C.2
Warranty:	Ten Year Limited Warranty

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.

