# **TK-LVLP Series**

oice, Data and Signaling Circuit Surge Protection







**DTK-2LVLPLV** 

**DTK-4LVLPX** 

#### **Product Features**

- Protect 1, 2, 4 or 8 pairs to match your specific configuration needs
- Series connection, parallel function adds no resistance to loop circuits
- Seven voltage levels available to protect all types of voice/data/signaling applications
- "SCP" models provide automatic resetting fuse and sneak current protection

## **Applications**

- 4-20mA Current Loops
- Alarm Panel NAC, SLC, PIV and IDC Loops
- Burglar Alarm Panels
- Speakers and Phones

#### **Accessories**

DIN Rail Kit (DTK-DRK)

**Selection Guide** 

**DITEK's DTK-LVLP** Low Voltage Line Protector series of signal, data and loop circuit surge protectors provide strong protection in a compact hard wired package. Models are available to protect up to 8 pairs. LVLAWG models can handle #14-#10 AWG wiring connections. Both are suitable for AC and DC circuits.

| Technical Specifications |  |  |  |  |
|--------------------------|--|--|--|--|
| Protection Modes:        | Line-Ground (All)  |  |  |  |
| Surge Current Rating:    | 2,000 Amps per pair (5V – 48V)<br>9,000 Amps per pair (75V – 130V) |  |  |  |
| Max. Continuous Current: | 5 Amps, 0.15 Amps (SCP)  |  |  |  |

#### **Mechanical Characteristics**

| Connection Method:        | Screw Terminals :<br>#22 - #16 AWG (LVLP),      |  |  |  |
|---------------------------|---|--|--|--|
|                           | #14 - #10 AWG (LVLAWG)                          |  |  |  |
| Housing:                  | ABS   |  |  |  |
| Operating Temperature:    | -40°F - 158°F (-40°C - 70°C)                    |  |  |  |
| Maximum Humidity:         | 95% non-condensing                              |  |  |  |
| Dimensions (1LVL – 4LVL): | 3.0L x 1.6"W x 1.6"H                            |  |  |  |
| Dimensions (1212 4212):   | (76mm x 41mm x 41mm)                            |  |  |  |
| Dimensions (8LVL):        | 4.8"L x 2.3"W x 1.5 "H<br>(122mm x 58mm x 35mm) |  |  |  |
| Weight:                   | 2.4 oz (68g)                                    |  |  |  |

### **Quality, Standards & Approval**

| Agency Approvals: | UL497A, UL497B            |  |  |  |
|-------------------|---------------------------|--|--|--|
| Warranty:         | Ten Year Limited Warranty |  |  |  |

| Example:            | DTK-2LVLPSCPLV          |               |
|---------------------|-------------------------|---------------|
| DTK- <mark>2</mark> | LVLP <mark>SCPLV</mark> | $\rightarrow$ |
|                     |                         | <b></b>       |

|         | Pa         |
|---------|------------|
| <b></b> | Se         |
|         | Sne<br>Ava |
|         | МС         |

| VOLTAGE LEVEL                              | D       | Х          | LV         | ОРХ   | SPK    | RUV    |
|--|---------|------------|------------|-------|--------|--------|
| Pairs Available:                           | 2, 4, 8 | 1, 2, 3, 4 | 1, 2, 4, 8 | 2, 4  | 2      | 2, 4   |
| Service Voltage:                           | 5V      | 12V        | 24V        | 48V   | 75V    | 130V   |
| Sneak Current Protection Available? (SCP): | Yes     | Yes        | Yes        | Yes   | No     | Yes    |
| MCOV:                                      | 8VDC    | 18VDC      | 38VDC      | 66VDC | 102VDC | 175VDC |
| Clamping Voltage:                          | 12V     | 22V        | 47V        | 82V   | 120V   | 204V   |

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions

Doc. Number: SPS-100030-001 Rev 8 02/16

©2016 DITEK Corp.









24 Volts

2 Pairs