

AD365/-IV and AD365A/-IV

Multi-Criteria Photo/Thermal/Infrared Detector



General Description

AD365/-IV and AD365A/-IV are plug-in addressable multi-criteria detectors that combine photoelectric, thermal, and infrared (PTIR) sensors in one unit to sense multiple components of a fire. This approach enables enhanced sensitivity to real fire with heightened immunity to nuisance particulates.

Multiple sensors and communication can greatly reduce nuisance alarms compared to single sensing methods. Sophisticated algorithms maximize the advantages of the sensor types. This detection strategy offers heightened immunity to nuisance particulates and enhanced sensitivity to real fire.

- Photoelectric sensors detect airborne particles associated with smoke.
- Thermal sensors detect heat and rate-of-rise (135°F fixed temperature threshold).
- The Infrared sensor discerns light patterns in the environment as an additional data point for alarm determination.

This ability to reject certain nuisance alarm triggers, such as theater smoke, supports the use of the detector in applications where moderate to heavy nuisance conditions exist that might cause single sensing detectors to trigger a false alarm.

The PTIR detector meets both UL 268 and UL 521 listing requirements and can indicate distinct smoke and heat alarms. This dual nature supports a local alarm setting for photoelectric detection and a general evacuation setting based on thermal detection. This can minimize work interruptions in multi-level buildings.

Features

- Multi-criteria detection
- UL 268 and UL 521 Listed
- New modern profile
- Analog communications
- Low standby current
- Rotary address switches
- Dual LEDs for 360° visibility
- Expanded color options
- LiteSpeed® protocol support on all models; LiteSpeed and CLIP protocol support on -IV models

Specifications

PHYSICAL

- Height: 2.0" (51 mm) installed in B300-6 base
- Diameter: 6.2" (156 mm) installed in B300-6 base; 4.1" (104 mm) installed in B501-WHITE/-IV/-BL base
- Weight: 3.4 oz. (95 g)
- Color: White
- Operating Humidity Range: 15% to 90% Relative Humidity, Non-condensing
- Operating Temperature Range: 32°F to 100°F (0°C to 38°C)
- Air Velocity: 0 to 300 ft./min. (0 to 91.4 m/min.)

ELECTRICAL SPECIFICATIONS

- Operating Voltage Range: 15 to 32 VDC
- Operating Current @ 24 VDC: 200 uA (one communication every 5 seconds with green LED blink on communication)



AD365 Multi-Criteria Detector installed in B200S-WH sounder base

- Maximum Alarm Current: 2 mA @ 24 VDC (one communication every 5 seconds with red LED solid on)
- Maximum Current: 4.5 mA @ 24 VDC (one communication every 5 seconds with amber LED solid on)
- Isolator Load Rating: 0.0063

Standards

The devices in this datasheet meet the standards of UL 268 .

Agency Listings and Approvals

The listings and approvals below apply to the AD365/-IV and AD365A/-IV. In some cases, certain modules may not be listed by certain approval agencies, or listing may be in process. Consult the factory for the latest listing status.

UL: S1059

FM Approved

CSFM: 7272-0075:0507

Ordering Information

"-IV" suffix indicates support of LiteSpeed and CLIP.

AD365: Multi-criteria photoelectric, thermal and infrared smoke detector, LiteSpeed, UL listed, white. For ivory, order AD365-IV (LiteSpeed and CLIP).

AD365A: Multi-criteria photoelectric, thermal and infrared smoke detector, LiteSpeed, ULC listed, white. For ivory, order AD365A-IV (LiteSpeed and CLIP).

BASES

B501-WHITE: 4" Mounting base, white

B501-WHITE-BP: 4" mounting base, white, 10-pack

B501-IV: 4" Mounting base, ivory

B501-BL: 4" Mounting base, black

B300-6: 6" Flanged mounting base, white
B300-6-BP: 6" Flanged mounting base, white, 10-pack
B300-6-IV: 6" Flanged mounting base, ivory
B200S-WH: Intelligent addressable sounder base, white
B200S-IV: Intelligent addressable sounder base, ivory
B200S-LF-WH: Intelligent addressable sounder base, low-frequency, white
B200S-LF-IV: Intelligent addressable sounder base, low-frequency, ivory
B224BI-WH: Isolator base, white
B224BI-IV: Isolator base, ivory
B224RB-WH: Relay base, white
B224RB-IV: Relay base, ivory

ACCESSORIES

SMB600: Surface mounting kit (flanged)
TR300: Trim ring, white
TR300-IV: Trim ring, ivory
CK300-IR: IR color kit (includes cover and trim ring), white, 10-pack
CK300-IR-IV: IR color kit (includes cover and trim ring), ivory, 10-pack
CK300-IR-BL: IR color kit (includes cover and trim ring), black, 10-pack
RA100Z: Remote LED annunciator
M02-04-00: Detector test magnet
M02-09-00: Telescoping test magnet

Fire•Lite® Alarms® and **LiteSpeed®** are registered trademarks of Honeywell International Inc.
©2019 by Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited.



This document is not intended to be used for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

For more information, contact Fire•Lite Alarms Phone: (800) 627-3473, FAX: (877) 699-4105.
www.firelite.com

Country of Origin: Mexico