



1000BaseSX / LX SFP Modules



	Wavelength	Media	Distance	TX Power (dBm)	RX Sensitivity (dBm)
MG-LC	850	MMF	220/550 m	-9.5 ~ -4	Max. -18
MG-LC10	1310	SMF	10 km	-9.5 ~ -3	Max. -20
MG-LC20BA	TX: 1310nm RX: 1550nm	SMF	20 km	-9.5 ~ -3	Max. -20
MG-LC20BB	TX: 1550nm RX: 1310nm	SMF	20 km	-9.5 ~ -3	Max. -20
MG-LC40	1310	SMF	40 km	-4 ~ +1	Max. -24
MG-LC60	1310	SMF	60 km	0 ~ +5	Max. -24
MG-LTX (1000)			100 m		

- Compliant with IEEE 802.3z 1000BaseSX/LX Gigabit Ethernet Standards
- Duplex LC Connector
- Hot Pluggable
- Class 1 Laser Product
- Industry Standard
- Single 3.3V Power Supply
- Cable Type: 62.5um MMF: 220 m ; 50um MMF: 550 m ; 9/10um SMF: 10 km
- Operating Temperature: 0 to 60C ; Storage Temperature: -40 to 85C ; Humidity: 10 to 90%

INAXSYS SECURITY SYSTEMS INC.
 8272 PASCAL GAGNON
 SAINT-LEONARD, QC H1P 1Y4
 ORDERS@INAXSYS.COM
 1-888-648-6648