

# Surface-Mount QuickPort® Boxes

## **APPLICATION**

The compact surface-mount box accepts QuickPort snap-in connectors. The box supports voice/data applications in office, retrofit, or other surface-mount environments. It includes an ID window, mounting screws, and adhesive, and is available in four colors: white, ivory, grey, and black.



## **SPECIFICATION**

The surface-mount box shall be small and low profile to accept up to twelve field-configurable QuickPort connectors. Base shall include cable anchor points. Mounting methods shall include screws, pressure sensitive adhesive, and magnets. Cover shall include an identification window, which also hides a userprovided #6 x 1/2-inch security screw. Construction shall be of high-impact fire-retardant plastic rated UL 94V-0. Box shall be cULus listed and compliant with ANSI/TIA-568-C. One and two-port housings shall comply with UL 2043 as suitable for use in air handling spaces per NEC 300-22(b)(c).

Page 1 of 2

## **FEATURES**

- · One and two-port housings are suitable for installation in air handling spaces (plenum)
- · User-provided cover screw can be installed for additional security
- · Compatible with all individual QuickPort modules
- Connector module can be pre-terminated prior to snapping into housing port
- 1-port blank included to close off unused port for 2-port box
- Designation label provided for identification purposes
- · Includes two self-tapping screws and pressure-sensitive adhesive

## **DESIGN CONSIDERATIONS**

- · Bottom, side, or rear cable entry options (rear cable entry recommended to help meet cable bend radius standards)
- Accepts magnet (41030-SMJ) for mounting on steel surfaces
- · Allows the use of different colored connectors for different applications to identify ports, 13 ANSI/TIA-606-B compatible connector colors available
- The 4-port box has mounting holes that are compatible with NEMA electrical boxes, covering the wall opening when mounted to single- gang NEMA boxes

## STANDARDS COMPLIANCE

ANSI/TIA-568-C **RoHS** compliant cULus 1863. 2043

## PHYSICAL SPECIFICATIONS

Dimensions:	See page two
Materials:	High-impact, fire-retardant plastic rated UL 94V-0
Mounting:	Screws (included), pressure-sensitive adhesive (included), or magnet (sold separately)

## **COUNTRY OF ORIGIN**

Mexico

#### WARRANTY INFORMATION

For a copy of Leviton product warranties, visit www.leviton.com/warranty.

Leviton Network Solutions 2222 - 222nd St. SE Bothell, WA 98021-4416	Asia / Pacific T +1.631.812.6228 E infoasean@leviton.com	Canada T +1.514.954.1840 E pcservice@leviton.com	Caribbean T +1.954.593.1896 E infocaribbean@leviton.com	China T +852.2774.9876 E infochina@leviton.com	<b>Colombia</b> T +57.1.743.6045 E infocolombia@leviton.com
tel 1-800-824-3005 tel +1-425-486-2222 appeng@leviton.com www.leviton.com	Europe T +33.6.8869.1380 E infoeurope@leviton.com	India / SAARC T +971.4.886.4722 E infoindia@leviton.com	Mexico T +52.55.5082.1040 E Isamarketing@leviton.com	Middle East & Africa T +971.4.886.4722 E Imeinfo@leviton.com	South Korea T +82.2.3273.9963 E infokorea@leviton.com


Copyright © 2015 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.



#### **ELECTRONIC FILES**


For CAD files, typical specs, or technical drawings (.DXF, .DWG), visit www.leviton.com.









41089-2xP




41089-4xP



41089-6xP



41089-12x



PART NUMBERS						
Description			WHITE	IVORY	GREY	BLACK
Surface-Mount QuickPort <sup>®</sup> Box, 1 Port			41089-1W	P 41089-1IP	41089-1GP	41089-1EP
Surface-Mount QuickPort Box, 2 Ports			41089-2W	P 41089-2IP	41089-2GP	41089-2EP
Surface-Mount QuickPort Box, 4 Ports			41089-4W	P 41089-4IP	41089-4GP	41089-4EP
Surface-Mount QuickPort Box, 6 Ports			41089-6W	P 41089-6IP	41089-6GP	41089-6EP
Surface-Mount QuickPort Box, 12 Ports			41089-12V	V 41089-12I	41089-12G	41089-12E
Page 2 of 2						A15 5104
Leviton Network Solutions 2222 - 222nd St. SE Bothell, WA 98021-4416	Asia / Pacific T +1.631.812.6228 E infoasean@leviton.com	Canada T +1.514.954.1840 E pcservice@leviton	<b>T</b> +1.	o <b>bean</b> 954.593.1896 ocaribbean@leviton.com	China T +852.2774.9876 E infochina@levito	

6045 ia@leviton.com

tel 1-800-824-3005 tel +1-425-486-2222 appeng@leviton.com www.leviton.com

Europe T +33.6.8869.1380 E infoeurope@leviton.com

India / SAARC T +971.4.886.4722 E infoindia@leviton.com Mexico T +52.55.5082.1040 E lsamarketing@leviton.com

Middle East & Africa T +971.4.886.4722 E Imeinfo@leviton.com South Korea T +82.2.3273.9963 E infokorea@leviton.com

Copyright © 2015 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

REGISTERED Quality Manufacture