

12VDC, 30W Power Supply

PW7725



Powers connected home devices by converting high voltage alternating current (AC) to low voltage direct current (DC)

features & benefits

- Package includes a DC power supply with 2 ft barrel connector plug and 1.5 ft AC power plug
- IEC C13/C14 connections
- Stacks neatly in enclosure with AC1031 power strip

specifications

General Info

Connection Type: DC Barrel
Type: Power Supply

Listing Agencies/Third Party Information

UN SPS C: 39121006

Dimensions

Height Metric: 3.1 cm
Height U S: 1.22"
Length U S: 3.86"
Length Metric: 9.8 cm
Width Metric: 4.5 cm
Width U S: 1.77 in

Cord Information

Cord Length Metric: 45.7 cm AC in, 6.1 cm DC out

Cord Length U S: 18" AC", 24.02" DC out

Technical Information

AC Voltage Input: 100-240VAC

Amps: 2.5A

Efficiency: 0.8

Humidity: Operating Humidity: 10% to 90%; Storage: 5% to 90%

Mounting: Enclosure

Operating Temperature Celsius: 0°C to 40°C

Operating Temperature Fahrenheit: 32°F to 104°F

Storage Temperature: -4°F to 185°F

Volts D C: 12 VDC Out

Watts: 30W

Number Of Receptacles: 1