

# PROXIMITY KP50 KEYPAD



## Box contents

- Plastic - Keypad clip on cover 50mm - Black
- Plastic - Keypad clip on cover 50mm - White
- Fitting kit - P50, UL
- Packaging - box insert - readers for icc-bx01 (rki)
- Packaging - box OD 190x175x55mm readers (ne3)
- Label - product serial number label 27x10mm
- Label - Tech support international
- Label - Void if seal is broken, 80x30mm
- Sales Code label, 27x20mm, Paxton, FCC and IC ID
- KP50 keypad proximity module

[Instructions - TOUCHLOCK K and KP series keypad UL](#)

<b>Specifications - PROXIMITY KP50 keypad</b>				
<b>Electrical</b>				
Operating voltage	10	12	14	V DC
Current consumption	70		180	mA
Carrier frequency		125		kHz
Clock & data bit period		600		µs
<b>System Specification</b>				
Cable type for extensions	Beldon 9540			
Maximum cable extension length			100	m
Read range: Keyfob			50	mm
Read range: Token/ISO card			80	mm
Read range: Watchprox			35	mm
Read range: Net2Air token			1100	mm
Backlit	Yes			

Additional colored bezels available	Yes		
Net2Air compatible	Yes		
<b>Environment</b>			
Operating temperature	-35	66	°C
Moisture resistance	IPX7		
Vandal resistance	Low		
<b>Dimensions</b>			
Cable length	5	m	
Width	50	mm	
Height	100	mm	
Depth	15	mm	