


REV	DATE	MODIFICATION	DRAWN
	2013/09/05		

1 ELECTRICAL:
 UL APPLICATIONS: 250 VOLTS AC MAX., AT 2 AMPS.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VOLTS AC.
 INSULATION RESISTANCE: 100M Ω.
 HUMIDIFICATION RESISTANCE: 20H @ MAX. AFTER ENVIRONMENTAL TESTING.

2 MECHANICAL:
 CABLE TO PLUG TENSILE STRENGTH: 19.6N/PCS MIN.
 DURABILITY: 200 MATING CYCLES.
 3 MATERIAL & FINISH:
 HOUSING: POLYCARBONATE, UL 94V-0 OR UL 94V-2.
 COLOR: TRANSPARENT OR OTHER COLOR ARE AVAILABLE.
 CONTACTS: COPPER ALLOY.
 CONDUCTOR: SOLID WIRE, 24AWG, 26 AWG.
 GOLD PLATING: 50μ"



BLADE:	Z
Drawing	
Mark	

		Quest Technology International, Inc. 11200 NW 138th St. Medley, FL 33178	
DIMENSION IN mm (Inch)	TOLERANCE UNLESS OTHERWISE SPECIFIED	材料名 MATERIAL	图号 FIG. NO.
.X±0.20	.X°±5°	PC	NMP-4225
.XX±0.10	.XX°±2°	名称 TITLE	名称 TITLE
公差 TOLERANCE	公差 TOLERANCE	MODULAR PLUG 6P/4C FOR ROUND CABLE, STRANDED AND SOLID WIRE	
审核 APPROVAL	检查 CHECKED	制图 DRAWN	比例 SCALE
		CathyLi	2/1
			张数 SHEET
			1/1
			更改 REV
			A

1 2 3 4 5 6 7
 1 2 3 4 5 6 7
 ST-DR-009A