

3-in-1 HD Video Baluns

EB-P101-01HQ HD Video Balun

EB-P101-20HQ HD Video Balun with 6" Pigtail

Features:

- 3-in-1 TVI / CVI / AHD video up to 1080p
- Transmits up to 1,443ft (440m) depending on format, resolution, and cable used
- PAL / NTSC / SECAM compatible
- Built-in TVS surge protection
- Anti-static and wave filters
- Lightning protection – Grade III
- 60dB Crosstalk and noise immunity
- Exceptional interference rejection
- Real-time transmission over low-cost Cat5e/6 cable instead of costly coaxial cable
- Quick-connect terminals for easy installation
- Small size allows mounting of multiple baluns behind a DVR
- Separate transmitter and receiver units to eliminate ghosting caused by interference in the signal



EB-P101-01HQ

EB-P101-20HQ




Specifications:


Model		EB-P101-01HQ	EB-P101-20HQ	
Video	Range*	TVI	720p: 623ft (190m) / 1080p: 623ft (190m)	
		CVI	720p: 1443ft (440m) / 1080p: 720ft (220m)	
		AHD	720p: 984ft (300m) / 1080p: 720ft (220m)	
	Video format	NTSC, PAL, SECAM		
	Frequency response	DC~42MHz		
Common mode rejection		60dB, 15kHz~42MHz		
Connections	Wire type	UTP (Unshielded Twisted Pair) 24~16 AWG		
	Wire category	Cat2~Cat6		
	UTP Connection	Nickel plated		
	Attenuation	1.5dB max.		
	Impedance	Coax, male BNC	75Ω@1MHz	
Screwless terminal		100Ω@1MHz ± 20Ω		
Protection	Surge protection	Renewable solid state surge protection		
	Video input	2KV (common mode), 10/700µs IEC6100-4-5/1955		
	Video output	2KV (differential mode), 10/700µs IEC6100-4-5/1955		
Other	DC Loop resistance	52Ω/1000' (18Ω/100m)		
	Differential capacitance	19pF/ft max. (62pF/m max.)		
	Power	No external power required		
	Operating temperature	-4°~158° F (-20°~70° C)		
	Storage temperature	-40°~305° F (-40°~150° C)		
	Humidity range	0~95 % (Non-condensing)		
	Case	ABS Plastic		
	Weight	1.4-oz (40g)		
	Cable length	N/A	5 ¹⁵ / ₁₆ " (150mm)	
	Dimensions	1 ³ / ₈ "x1 ¹¹ / ₁₆ "x3 ³ / ₄ " (35x17x19 mm) <i>Excluding BNC connector</i>	1 ¹ / ₂ "x3 ³ / ₄ "x1 ³ / ₁₆ " (38x19x20 mm) <i>Housing only</i>	

Dimensions:

EB-P101-01HQ



EB-P101-20HQ



*Actual range depends on format, resolution, and cable quality.

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com




Copyright 2016 © SECO-LARM U.S.A., Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®

PI_EB-P101-xxHQ_161021.docx


Sample Applications:

Single Pair of Passive HD Video Baluns



Note: Shorter range may result when used with a DVR.

Multiple CCTV Cameras over a Single Cat5e/6 Cable



Note: Shorter range may result when used with a DVR.

Also Available from SECO-LARM:

Ethernet Extenders



IPB-A1100Q shown

Power Supplies



PS-U0906-PULQ shown

Surge Protectors



VS-1V22AQ shown

VPD Combiners



EB-P304-01EQ shown

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright 2016 © SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®

PI_EB-P101-xxHQ_161021.docx