

# 4-in-1 HD TVI, CVI, AHD, Analog Corner-Mount Camera

#### EV-Y4201-A2SQ

The **ENFORCER** 4-in-1 HD TVI, CVI, AHD, Analog Corner-Mount Camera has a discreet, low-profile appearance and a wide-angle lens, making it perfect for elevators and office corners.

#### Features:

- 1/2.9" 2MP Sony CMOS
- Full HD (1920x1080) resolution
- True Day & Night function with ICR mechanism
- 3D-NR (3D Noise Reduction)
- DWDR (Digital Wide Dynamic Range)
- Built-in internal joystick OSD control
- Vandal-resistant metal front panel
- Weatherproof (IP65)
- 30 Covert IR LEDs for discreet monitoring

















#### 3D Digital Noise Reduction:

**DNR Off** 







## **Digital Wide Dynamic Range:**

**DWDR Off** 







Simulated images


# FC C & Fish Copyright © 2016 SECO-LARM U.S.A, Inc. All rights reserved. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to

change prices and specifications without notice. SECO-LARM is not responsible for misprints. SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI AL

### SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA, 92606 **Phone:** (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com





### **Specifications:**

Housing color		Silver
Туре		Corner-Mount Camera
Formats		TVI (default) / CVI / AHD / Analog
CMOS		1/2.9" 2MP Sony CMOS
Resolution (HD)		1920x1080
TV Lines (Analog)		1200TVL
Onboard OSD control		Yes
Megapixels		2MP
Lens		2.9mm ICR
Viewing angle		130°
# of IR LEDs		30 (940nm LEDs)
IR Range		Up to 82ft (25m)
FPS		30FPS
F Stop		F1.8
Minimum illumination	(IR On)	0Lux
	(IR Off)	Color: 0.2Lux/F1.8, B/W: 0.02Lux/F1.8
Gamma correction		0-1
S/N Ratio		50dB
DSS (Digital Slow Shutter)		Yes
Shutter control		Auto
Gain control		Auto
White balance		Auto, Day & Night
Operating voltage		12VDC
Current draw	(IR On)	400mA
	(IR Off)	80mA
IP Rating		IP65
Operating temperature		14°~122° F (-10°~50° C)
Dimensions		7 <sup>1</sup> / <sub>2</sub> "x5 <sup>1</sup> / <sub>2</sub> "x1 <sup>11</sup> / <sub>16</sub> " (190x140x43 mm)
Weight		13.75-oz (390g)