







....

PRODUCT FEATURES

- Cast stainless steel with 11 EPDM rubber keys
- · Weatherproof and vandal resistant
- 12V or 24V/ AC or DC current
- · Mounts on a narrow mullion
- Audible keystroke echo
- True 10 digit operation (keys are not paired)
- · 59 users with multiple entry codes
- User code and hard code disable feature
- · Passage Mode and Lockout Mode
- 5 Amp DPDT relay
- Request-to-exit (REX) input
- 16 ft. [4.8m], 12 conductor, 22 gauge keypad cable
- 3 LEDs and a bell button

1-1/2" [38mm]

• MagnaCare Lifetime Replacement No Fault Warranty

PRODUCT OPTIONS

- Cover plate
- Keypad available as system or separately

SPECIFICATIONS

• CE: EN 50091-1, EN 61000-6-2 Approved

Dimensions: Keypad: 1-1/2"W x 7"H x 7/8"D

Enclosure: 6"W x 8"H x 3"D

Electrical:

7mA at rest; 160mA active at 12VAC or 12VDC

20mA at rest; 190mA active at 24VAC or 24VDC


Operating Temperature: CPU: +32 to +158F [0 to +70C]

Keypad: -22 to +158F [-30 to +70C] Indoor or Outdoor use

Shipping Weight:

5lbs [2.27kg] Finishes:

US32D/630 - Satin Stainless Steel BK - Black



DK-26 Digital Keypad System

Digital Control System for Narrow Stile Applications

The DK-26 digital keypad system provides medium/ high security control of electric locks in one or two door applications where doors have the same control needs. The fully weatherproof, rugged stainless steel keypad can be mounted in most outdoor environments. Encased in a separate enclosure for secure installation, the full-featured, easy to program, DK-26 is ideal for narrow stile applications.

>> MODELS		PART # Description
DK-26BK	Digital Keypad System - Narrow Stile, Black Anodized	
DK-26SS	Digital Keypad System - Narrow Stile, Satin Stainless	
DK-26PBK	Digital Keypad Pad - Narrow Stile, Black Anodized	
DK-26PSS	Digital Keypad Pad - Narrow Stile, Stainless Steel	

1

ACCESSORIES for DK-26





DK26-CPSS » COVER PLATE

- Allows DK-26 and DK-37 to be mounted over a single gang box
- MagnaCare Lifetime Replacement No Fault Warranty



LIFE

MAGNACARE WARRANTY