

## **SECURITRON GLI**

# Electromechanical Gate Solution Offers One Ton of Holding Power

The heavy duty GL1 Electromechanical Gate Lock provides weather-resistant access control for a wide range of gate applications. The GL1 provides 2,000 lbs of holding force for electrical and manually operated indoor or outdoor gates where preload is a concern.

#### **Ideal Applications**

Swinging Gates



Sliding Vehicle Gates




Pedestrian Gates



Stock Gates



Interior Cribs



**Remote Field Gates** 



>> MODELS		PART#   Description
GL1-FL	Gate Lock, 12/24VDC, Standard Fail Locked	
GL1-FS	Gate Lock, 12/24VDC, Standard Fail Safe	
GL1-FLM	Gate Lock, 12/24VDC, Monitored Fail Locked	
GL1-FSM	Gate Lock, 12/24VDC, N	Monitored Fail Safe
GMC	Gate Lock Mortise Cylin	nder

**SECURITRON ASSA ABLOY** 



GL1 Electromechanical Gate Lock

### **Specifications**

Patent: 8,047,582

#### **Holding Force**

• 2,000 lbs [907kg]

#### **Dimensions**

2-3/4"L x 7-1/4"W x 3-1/4"D

#### **Electrical**

- 12 Volts Initial (Peak): (~1.0 sec.) @ 870mA -Reduced: 290mA Power
- Consumption: 3.5 Watts
- 24 Volts Initial (Peak): (~1.0 sec.) @ 720mA -Reduced: 170mA Power
- Consumption: 4.1 Watts

#### Operating temperature

• -58 to +167F [-50 to +75C] Indoor or outdoor use

#### **Shipping Weight**

6 lbs [2.72kq]



- 2,000 lbs Holding Force
- 100 lbs of Preload
- **Key Override Ready**
- **Automatic Dual Voltage**

## **Electromechanical Gate Lock**


#### **PRODUCT FEATURES**

- · 2,000 lbs holding force
- Operates under preload up to 100 lbs
- · Automatic dual voltage no field adjustment required
- · Accepts a standard mortise cylinder with Adams Rite MS cam for manual key override (not included, see spacer quide below)
- Self-aligning receiver (+/- 1/2" horizontally) helps compensate for gate misalignment and sag
- Tamper resistant cast housing
- Optional latch status monitor
- Surface mount
- MagnaCare® Lifetime Replacement No Fault Warranty

### Flex-Mount Gate Lock Bracket Kits (FMK)

Bracket Kits Extend Access Control to Gates and Fences.

The FMK Flex-Mount Bracket System is an intuitive set of mounting brackets designed exclusively for use with the M62FG Magnalock® and GL1 Gate Lock. Pre-formed post channels and plates of varying lengths make it easy for you to assemble a professional looking, high-security gate lock mounting platform in minutes, without special tools.





Cylinder Length	Spacer Required
1"	1/4″
1-1/8	3/8"
1-1/4"	1/2"

SMC-0564-0215





