

- GL1 Gate Lock

# **SECURITRON GLI Electromechanical Gate Solution Offers One Ton of Holding Power**

The heavy duty GL1 Electromechanical Gate Lock provides weather-resistant access control for a wide range of gate applications. The GL1 provides 2,000 lbs of holding force for electrical and manually operated indoor or outdoor gates where preload is a concern.

#### **Ideal Applications**

Swinging Gates















ASSA ABLOY, the global leader in door opening solutions © 2015, Hanchett Entry Systems, Inc., an ASSA ABLOY Group company.

# ASSA ABLOY

JECURITRON

SECURITRON.COM **1.800.MAGLOCK** 



GL1 Electromechanical Gate Lock

### **Specifications**

Patent: 8,047,582

#### **Holding Force**

• 2,000 lbs [907kg]

#### **Dimensions**

2-3/4"L x 7-1/4"W x 3-1/4"D

#### **Electrical**

- 12 Volts Initial (Peak): (~1.0 sec.) @ 870mA -Reduced: 290mA Power
- Consumption: 3.5 Watts
- 24 Volts Initial (Peak): (~1.0 sec.) @ 720mA -Reduced: 170mA Power
- Consumption: 4.1 Watts

#### **Operating temperature**

 -58 to +167F [-50 to +75C] Indoor or outdoor use

#### **Shipping Weight**

• 6 lbs [2.72kg]



- 2,000 lbs Holding Force
- 100 lbs of Preload
- Key Override Ready
- Automatic Dual Voltage

# GLI Electromechanical Gate Lock

## **PRODUCT FEATURES**

- 2,000 lbs holding force
- Operates under preload up to 100 lbs
- Automatic dual voltage no field adjustment required
- Accepts a standard mortise cylinder with Adams Rite MS cam for manual key override (*not included, see spacer* guide below)
- Self-aligning receiver (+/- 1/2" horizontally) helps compensate for gate misalignment and sag
- Tamper resistant cast housing
- Optional latch status monitor
- Surface mount
- MagnaCare<sup>®</sup> Lifetime Replacement No Fault Warranty

#### Flex-Mount Gate Lock Bracket Kits (FMK) Bracket Kits Extend Access Control to Gates and Fences.

The FMK Flex-Mount Bracket System is an intuitive set of mounting brackets designed exclusively for use with the the M62FG Magnalock<sup>®</sup> and GL1 Gate Lock. Pre-formed post channels and plates of varying lengths make it easy for you to assemble a professional looking, high-security gate lock mounting platform in minutes, without special tools.



Cylinder Length	Spacer Required
1"	1/4″
1-1/8	3/8″
1-1/4″	1/2″

GL1 with FMK-SW for swinging gates

SMC-0564-0215





1.800.MAGLOCK

SECURITRON.COM