






Touch Sense Plate (SP-1)

<u>Application</u> - The SP-1 uses patented touch sensing technology to create a push panel with no moving parts. For indoor use only, the unit is oversized so that it can be mounted over a single gang cut-out. A three part vinyl decal is included and a red LED is incorporated in the backbox.



Features and Benefits


- DPST 2 Amp rated relay
- Internal 0-25 second timer
- Built in redundant button

Specification Data

Current Draw: 40mA at rest, 25mA releasing

Voltage: 12 or 24 VDC

Operating Temperature: +32 to +110F [0 to +43C]
Warranty: MagnaCare Lifetime Replacement Warranty



How To Order

Part # Description

SP-1 Touch Sense Plate

SP-1LH Touch Sense Plate Handicapped Sticker only

SP-1L Replacement Touch Sense Plate Sticker only

Approvals and Listings

- TSB-3 & TSH Underwriter's Laboratories: File SA6635 Vol. 2 (UL 294 & NFPA 101)
- TSB-3 & TSH City of New York MEA: 251-95E & 254-95E
- TSB-3 & TSH California State Fire Marshall: 3774-0923:102, :103
- TSB-3 Underwriter's Laboratories: File SA6635 Vol. 1
- TSB-3 CE: EN 50081-1 (92) & EN 61000-6-2 (99)