

Honeywell



SK-FIRE-CO

Advanced Combination Fire and CO Detector

The SK-FIRE-CO is a plug-in, addressable device that provides both fire and carbon monoxide (CO) detection. For fire, the detector combines four separate sensing elements in one unit (smoke, CO, light/flame, and heat) to sense multiple components of a fire. This approach enables enhanced sensitivity to real fire with heightened immunity to nuisance particulate. For CO, the detector's electrochemical sensing cell creates a separate signal for life safety CO detection.

Released through the incomplete burning of various fuels, CO is a colorless, odorless and deadly gas that is virtually impossible to detect with the human senses. Because the potential exists for dangerous levels of CO to accumulate in almost any building, legislation mandating the use of CO detection in commercial spaces continues to increase across the U.S. and Canada. The SK-FIRE-CO is listed to the UL 2075 standard for system-connected life safety carbon monoxide monitoring.

The SK-FIRE-CO should be used in conjunction with the B200S/B200S-LF intelligent sounder base (sold separately), which can generate either a Temp 3 pattern for fire or a Temp 4 pattern for CO alarm indication. With each sounder base carrying a unique address, the FACP can then command an individual sounder, or a group of sounders, to activate. The command set from the panel can be tailored to the specific event, allowing selection of tone, and group.

SK-FIRE-CO can also be used with the B210LP 6" standard



SK-FIRE-CO

FEATURES & BENEFITS

- Unique ability to detect all four major elements of a fire, smoke, carbon monoxide (CO), light/flame, heat
- Separate CO detection signal
- Highest nuisance alarm immunity
- Automatic drift compensation of smoke sensor and CO cell
- Uses only one address on the SLC
- RealTest® CO testing capability
- UL 268 and UL 2075 listed
- Separates audible signal for fire or CO alarm when used with B200S/B200S-LF base
- CO cell end-of-life warning and fault
- CSFM listed

SK-FIRE-CO Technical Specifications

PHYSICAL

Diameter: 6.875" (17.46 cm) installed in a B200S base

Height: 3.46" (8.79 cm) installed in B200S base

Shipping Weight: 4.6 oz

Color: Ivory

OPERATING

Temperature Range: 32° F to 100° F (0° C to 38° C)

Humidity: 15 to 90% relative humidity (non-condensing)

Air Velocity: 0 to 4,000 ft/min (0 to 20 m/sec)

ELECTRICAL

Operating Voltage: 15 to 32VDC

SLC Standby and Alarm Current: 300µA

SENSITIVITY SETTINGS

Sensitivity settings are programmable through zone programming.

Low: 4% per foot (30.48 cm) of smoke. Used in equipment rooms, kitchens, paint shop.

Medium: 3% per foot (30.48 cm) of smoke. Moderately clean environments: Used in hotel rooms, dorm rooms.

High: 2% per foot (30.48 cm) of smoke. Clean environments: Used in offices.

Warning: After the CO cell has reached the end-of-life, the CO sensor no longer provides life safety protection. However, when the fire detector enters Photo, Thermal, Infrared (PTIR) mode, the following sensitivities apply:

Level 1: 1% per foot (30.48 cm) of smoke. Very clean environments- Used in laboratories.

Level 2: 2% per foot (30.48 cm) of smoke. Clean environments - Ued in offices.

Level 5: 3% per foot (30.48 cm) of smoke. Moderately clean environments- Used in hotel rooms, dorm rooms.

Level 6: Thermal alarm at 135° F (57° C).

CO Monitoring UL Standard Reference - Alarm Thresholds are as follows:

Parts Per Million	Detector Response Time
70 ± 5 ppm	60-240 min
150 ± 5 ppm	10-50 min
400 ± 10 ppm	4-15 min

Note: Per UL Standard 2075, the SK-FIRE-CO has been tested to the sensitivity limits defined in UL Standard 2034.

ORDERING INFORMATION

SK-FIRE-CO: Combination Fire and CO Detector (base not included).

OPTIONAL ACCESSORIES

B200S: Intelligent sounder base

B200S-LF: Low Frequency Intelligent sounder base

B210LP: 6" mounting base

B200SR: Sounder base

B224RB: Relay base

M02-04-01: Detector test magnet

M02-09-01: Telescoping test magnet

COMPATIBILITY

The SK-FIRE-CO is compatible with the following Honeywell Silent Knight fire alarm control panels:

6820: Addressable fire alarm control panel

6820EVS: Addressable fire alarm control panel with an emergency voice system.

6808: Addressable fire alarm control panel

6700: Addressable fire alarm control panel

5700: Addressable fire alarm control panel

5808: Addressable fire alarm control panel

5820XL: Addressable fire alarm control panel

5820XL-EVS: Addressable fire alarm control panel with an emergency voice system.

For a complete listing of all compliance approvals and certifications, please visit www.silentknight.com.

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation.

Silent Knight®, System Sensor® and Honeywell® are registered trademarks of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For Technical Support, call 800-446-6444.

For more information

Learn more about Honeywell Silent Knight and other products by visiting www.silentknight.com

Honeywell Silent Knight

12 Clintonville Road
Northford, CT 06472
800-328-0103