

Keystone Stainless Steel Faceplates

Signamax Connectivity Systems offers one of the broadest selections of field-configurable, flush-mount faceplates and multimedia surface-mount boxes. From single-gang faceplates to multimedia surface-mount multi-port boxes, Signamax has the solutions to fit your needs.

ORDERING INFORMATION

Single-Gang Stainless Steel Faceplates

Single-gang brushed stainless steel faceplates allow mounting any combination of keystone jacks and multimedia modules. These faceplates allow for flush mounting of jacks and for a clean appearance. Stainless steel faceplates are ideal for use in environments that require greater durability and a sanitary, easy-to-clean solution.

Part Number	Description
SSKF-1	1-Port Single-Gang Stainless Steel Faceplate
SSKF-2	2-Port Single-Gang Stainless Steel Faceplate
SSKF-3	3-Port Single-Gang Stainless Steel Faceplate
SSKF-4	4-Port Single-Gang Stainless Steel Faceplate
SSKF-6	6-Port Single-Gang Stainless Steel Faceplate
SSKFL-1	1-Port Single-Gang Stainless Steel Faceplate with Labeling
SSKFL-2	2-Port Single-Gang Stainless Steel Faceplate with Labeling
SSKFL-3	3-Port Single-Gang Stainless Steel Faceplate with Labeling
SSKFL-4	4-Port Single-Gang Stainless Steel Faceplate with Labeling
SSKFL-6	6-Port Single-Gang Stainless Steel Faceplate with Labeling



Stainless steel wall mount phone plate provides a clean, easy-to-install method for mounting any wall mountable phone. Plates are standard sized and with durable mounting posts.

Part Number	Description
SSKF-1P	1-Port Stainless Steel Keystone Wall-Mount Phone Plate

Double-Gang Stainless Steel Faceplates

Double-gang brushed stainless steel faceplates are available in 8- and 12-port versions and allow for flush mounting of jacks and for a clean appearance. Stainless steel faceplates are ideal for use in environments that require greater durability and a sanitary, easy-to-clean solution.

Part Number	Description
DSKF-8	8-Port Double-Gang Stainless Steel Keystone Faceplate
DSKF-12	12-Port Double-Gang Stainless Steel Keystone Faceplate



SPECIFICATIONS

CONSTRUCTION

Plate: stainless steel, JIS SUS 304 (equivalent to EN 1.4301, SAE 304, UNS 30400)

Mounting posts: high impact thermoplastic, UL94V-0 fire retardant

OVERALL DIMENSIONS

Single gang: W 69.9 mm x H 114.3 mm (W 2.75 in x H 4.50 in)
Double gang: W 116.8 mm x H 114.3 mm (W 4.60 in x H 4.50 in)

MOUNTING DIMENSIONS

Mounting screw holes distance: 83.3 mm (3.28 in)

• KEYSTONE MODULE MOUNTING DIMENSIONS

Mounting dimensions: standard keystone footprint

Panel opening: 14.7 mm (0.579 in) x 19.30 mm (0.760 in)

ENVIRONMENTAL

Operating temperature: $-14^{\circ}F - 140^{\circ}F (-10^{\circ}C - +60^{\circ}C)$

www.signamax.com