

Test Set

RUGGED BUT COST-EFFECTIVE, THE B600 PROFESSIONAL TELEPHONE TEST SET FEATURES HI-Z MONITORING, PULSE AND TONE (DTMF), 10 NUMBER SPEED DIAL AND POLARITY INDICATION IN A RUGGED DOUBLE MOLDED HOUSING.





1-855-SWT00LS (855-798-6657)



Southwiretools.com



Professional Telephone Test Set







- "HI-Z" MONITORING WILL NOT DISRUPT NETWORK TRAFFIC
- HIGH AND LOW VOLUME SETTINGS,
 POLARITY LED, TONE & PULSE MODES
- ABN (ANGLED BED OF NAILS) CLIPS
 WITH RUGGED RJ45 AND RJ11 PLUGS
- LAST NUMBER REDIAL AND MEMORY
 TO STORE UP 10 PHONE NUMBERS

ELECTRICAL

Operating Temperature	32°F to 122°F (0°C to 50°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Humidity	10% to 90% non-condensing
Loop Limit	2.4KΩ maximum at 48VDC (nominal 15 mA minimum loop current)
DC Resistance (Talk Mode)	150Ω typical at 80mA current
AC Impedance (Monitor Mode)	HI Z: 100KΩ @ 1KHz RING: 600Ω @ 1KHz

ROTARY DIAL OUTPUT

Pulsing Rate	20pps +/-0.5pps
Percent Break	60% +/-2%
Interdigit Interval	500 ms typical
Leakage During Break	>50ΚΩ

DTMF OUTPUT

	Tone Frequency Error	+/-1% maximum
Ī	Level per Tone Pair	+2dBm maximum,-8dBm minimum
Ī	High versus Low Tone Difference	4dBm maximum

PHYSICAL

Dimensions	10.12" X 2.43" X 2.49" (25.7 X 6.17 X 6.33 cm)
Weight	11.0 oz (312.8 g)
Battery	CR2032 (included)

A WARNING: For use on analog phone circuits only.



Professional Telephone Test Set, ABN Test Leads, CR2032 Battery



BUILT FOR DURABILITY. BUILT FOR RELIABILITY. BUILT FOR WORK."

1-855-SWTOOLS (855-798-6657)



Scan code to see more

Southwiretools.com