

Preliminary Specifications: VTD-THD2RMS

Transcendent 2.1 Megapixel Indoor/Outdoor 4-IN-1 HDA Vandal Dome Camera w/30 IR LEDs & Motorized Varifocal Lens



FEATURES:

- 1/2.8" 2.1 Megapixel Progressive Scan CMOS Sensor
- Advanced Starlight Technology Offers Dramatically Higher Sensitivity to Light Producing Color Images in Very Dark & Night Scenes
- HD-TVI / AHD / CVI / CVBS (Selectable) Video Output
- 2.8-12mm Motorized Varifocal Lens
- 30 Dynamic Intensity LEDs with 100' IR Range
- True Wide Dynamic Range (WDR)
- True Mechanical Day/Night function by ICR
- 2D-DNR Noise Reduction
- IP66 Weather Resistance & IK10 Impact Resistance Rating
- Supports Up The COAX Control
- Over 1500' HD Video Transmission (Depending on cable characteristics and integrity)
- Optional Wall Mount (VT-TWM03) & Junction Box Mount Available (VT-TJB02)
- Available in Ivory or Charcoal Gray
- 12VDC Operation
- 3 Year Warranty

Transcendent Series High Definition 1080P HD-TVI, AHD, CVI, and CVBS 4-IN-1 Cameras offer unprecedented performance and value.

These simple, easy to install, attractively styled, analog HD Cameras transmit over your existing Coaxial cable at distances up to 1500'.

5-In-1 Digital Video Recorders Supporting HD-TVI / AHD / CVI / 960H Cameras



Transcendent Series 4, 8, 16 or 32 Channel 5-In-1 Digital Video Recorders Support HD-TVI / AHD / CVI / 960H Cameras as well as IP Cameras.



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

An Eye On
Innovation

Preliminary Specifications: VTD-THD2RMS

Transcendent 2.1 Megapixel Indoor/Outdoor 4-IN-1 HDA Vandal Dome Camera w/30 IR LEDs & Motorized Varifocal Lens

Specifications	
Image Sensor	1/2.8" 2.1 Megapixel Progressive Scan CMOS Sensor with Advanced Starlight Technology
Signal System	PAL/NTSC
Effective Pixels	1920 x 1080
Resolution	HD-TVI / AHD / CVI: 2.1 MegaPixel / CVBS: 960H
Video Output	HD-TVI / AHD / CVI / CVBS (Selectable)
Lens	2.8-12mm Motorized Varifocal
Day/Night	True Day/Night by ICR
Min. Illumination	Color: 0.001 lux@F1.2, AGC ON / B/W: 0 lux (with IR ON)
IR LEDs	30 Dynamic Intensity LEDs
IR Distance	100'
S/N Ratio	≥52dB (AGC Off)
WDR	True WDR
Defog	YES
Digital Noise Reduction (DNR)	2D-DNR
White Balance	Auto (AWB)
BLC	YES
Up the COAX Control (COC)	YES
Transmission Distance	Up to 1500' (Depending on cable characteristics & integrity)
Power Input	12VDC
Power Consumption (12VDC)	IR Off: 120mA / IR On: 480mA
Resistance Rating	IP66 / IK10
Operation Conditions	-4 ~ 122 / 10% ~ 90% Humidity
Weight	34.22 oz. / 2.14 lbs. / 970g
Dimensions	5.91" x 4.49" (150 x 114mm) Dia x H



VT-TWM03
Wall Mount for Transcendent
30 IR LED Vandal Domes
and Varifocal Turret Cameras



VT-TJB02
Junction Box for Cable
Management for use with
Transcendent 30 IR LED
Vandal Domes