

VTD-TND5RFE-2 Transcendent Series 5MP Indoor/Outdoor WDR IP Vandal Dome Camera with 16 IR LED Illumination



FEATURES:

- 1/2.7" 5.0 MegaPixel CMOS Image Sensor
- Up to 20fps live view @ 5.0 MegaPixel (2592x1944)
- 2.8mm Fixed Iris Lens
- 16 Infrared LEDs with 65' IR Range
- Digital Wide Dynamic Range (D-WDR)
- True Mechanical Day/Night function by ICR
- XD-DNR (3D & 2D DNR) Noise Reduction
- Features: On Board Motion Detection, Privacy Masking, Region of Interest, Exception, Line Crossing, Intrusion, Object Detection / Removal (Museum Search)
- H.265, H.264 & MJPEG Compression
- Remote Viewing via CMS, Internet Explorer, and iOS & Android Apps
- ONVIF Compliant
- IP66 Weather Resistance
- Optional Junction Box Mount (VT-TJB03A) and Wall Mount (VT-TWMT3) Available
- 12VDC & PoE (Power over Ethernet) Operation

Transcendent Series High Definition 5 MegaPixel IP Network Cameras offer unprecedented performance and value.

These simple, easy to install, attractively styled, IP Network Cameras transmit over remote viewing via CMS, Internet Explorer, and iOS & Android Apps.

Use with VITEK Transcendent Series Real Time Network Video Recorders



Transcendent 4, 8, 16, 32, 64, and 128 Channel 8 MegaPixel H.265 Real Time Network Video Recorders with 4K HDMI Output.



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

An Eye On Innovation

VTC-TND5RFE-2 Transcendent Series 5MP Indoor/Outdoor WDR IP Vandal Dome Camera with 16 IR LED Illumination

Detailed Specifications

| | |
|-----------------------------|---|
| Image Sensor | 1/2.7" 5.0 MegaPixel CMOS |
| Image Size | 5 MegaPixel 2592x1944 |
| Resolution | 5MP (2592x1944), 4MP (2592x1520), 2K (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240 |
| Min. Illumination | 0 Lux (IR LED ON) |
| Lens | 2.8mm Fixed Iris Lens |
| Day / Night | True Day / Night by ICR |
| IR LEDs / IR Distance | 16 / 65' |
| Video Compression | H.265 / H.264 / MJPEG |
| Multi-Stream | 1~20fps: 5MP, 1~30fps: 4MP, 2K, 3MP, 1080P, 720P |
| WDR | Digital WDR |
| DNR | XD-DNR (3D-DNR & 2D-DNR) |
| Quality | VBR (Five Levels of Adjustment) / CBR (Adjustable) |
| Image Setting | Saturation, Brightness, Contrast, WDR, Noise reduction |
| Smart Alarm | Motion Alarm |
| ROI | Region of Interest (Up to 3 areas can be configured) |
| Features | Line Crossing, Exception, Intrusion Detection, Object Detection / Removal (Museum Search) |
| Network | RJ45 |
| Remote Viewing | CMS / Web Browser / Mobile (iOS/Android) |
| Supported Browsers | Microsoft Internet Explorer, Chrome and Firefox with IE Tab |
| Connection Protocol | ONVIF |
| Weather Resistance / Impact | IP66 Weather Resistance / IK10 Impact Rating |
| Power Input | 12VDC / PoE |
| Power Consumption (12VDC) | IR On: 120mA / IR Off: 360mA |
| Power Consumption (PoE) | < 6W |
| Working Environment | -4 ~ 122 / 10% ~ 90% Humidity |
| Weight | 20.92 oz. / 1.31 lbs. / 593g |
| Dimensions | 4.57" x 3.58" (116mm x 91mm) Dia x H |



VT-TWMT3
Optional Wall Mount for use with Select Transcendent Vandal Dome Cameras



VT-TJB03A
Optional Junction Box for Cable Management for use with Select Transcendent Vandal Dome Cameras and Turret Style Cameras